

## **USS ARES NCC-1650** (Specifications as of 2245)

Ares-class Battlecruiser; commissioned: 2243; withdrawn: 2262

### **HULL DATA**

structure: 35  
size/decks: 5/10; (average deck ht. 2.5 meters)  
L/B/H: 238/127/49  
complement: 150-200

### **TACTICAL DATA**

phaser banks: Type I (x14/C); fire arcs: 2 f, 2 f/p, 2 f/s, 2 p, 2 s, 1 a/p, 1 a/s, 2 a  
penetration: 4/3/3/0/0  
torpedo launchers: Mk 10 if (x8/C); fire arcs: 4 f, 4 a  
penetration: 4/4/4/4/4  
deflector shield: PFF 2a (B)  
protection/threshold: 14/3

### **PROPULSION DATA**

impulse system: SBE (0.5c) (D)  
warp system: PB-20 (5.2/6.2/7.2) (D)

### **OPERATIONAL DATA**

cargo units: 60  
life support: Class 3 (D)  
operations system: Class 3e (E)  
sensor system: Class 3 (+3/+2/+1/0/0) (C)  
shuttlebay: 1 aft  
shuttlecraft: 5 size worth  
tractor beams: 1 fv, 1 ad  
transporters: 4 standard, 4 emergency, 4 cargo

### **MISCELLANEOUS DATA**

maneuver modifiers: +4 C, +0 H, +2 T  
traits: Prototype (shields +1 protection; reflected above), Prototype (sensors, -1 reliability; reflected above), Prototype (operations +1 reliability; reflected above), Design Defect (missile; reflected above), Intricate System (phasers, torpedo launchers, deflector shields; **Effect:** All repair attempts on this particular system suffer +4 to the TN.), Flagship (+2 C; reflected above), Famous (R 23)